





FLIP FLOW
optional

METRIC



Screen box
(L x W)

5000x
1500mm



Capacity
up to
450t



WEIGHT
28,5T

The contractors choice due to heavy duty performance, compact transport and high productivity.

Its long screen deck is perfect for precision screening from scalping to fine screening.

The K5 has a large range of screening media available incl. the Bivitec flip flow screen box for very difficult to process materials. Perfect service access and a walkway on the left side of the screen box, which is liftable and can be set in several inclinations.

2 or 3-way split position possible

Extra long
screenbox



Applications

Pre-screening/scalping

Screening behind or before a crusher

Top soil

Separation of "sticky" aggregate

Construction and demolition waste

Sand and gravel

Quarrying and mining

Coal

Wood

Recycling landfill

And others

Increased uptime and longer service intervals due to Long Life Grease

Maintenance free Return drum bearings (greased for life)

Automatic transport locking system on side conveyors

- Hydraulic folding hopper of HB 450 steel

- Superior level of surface treatment

- Accessible doors and panels on all sides of the machines for easy maintenance and repair

- Standard equipped with heavy duty apron feeder

Technical specifications		
Capacity up to		450 t
Weight		28,5 t
Screen box (l x w)		5000x1500 mm & 5000x1350 mm
Feed hopper in HB450		7 m³
Hydraulic folding hopper for transport		•
Heavy Duty Plate Apron Feeder		3150 x 1120 mm
Loading height		
	open back wall	2645 mm
	half open back wall	3040 mm
	closed back wall	3400 mm
	Side loading length	4200 mm
Screen box (l x w) standard & bivitec flip flow		
Upper deck m²		7,5 m² & 6,75m²
Middle deck m²		/
Lower deck m²		7,08 m² & 5,4m²
Hydraulic liftable screenbox		•
Screen box can be set in several inclinations		6
Standard walkway beside screenbox		Left side
Standard Long Life Grease: grease interval every 250 h		•
Conveyor belts (l x w) & discharge height		
Oversize belt conveyor (discharge height)		5000 mm x 1200 mm (3100mm)
Fine fraction belt conveyor (left) (discharge height)		8350 mm x 900 mm (4380mm)
Middle fraction belt conveyor (right) (discharge height)		8280 mm x 800 mm (3790 mm)
Track-unit: Length, total width, track shoe width		
2-speed track drive		3310, 2500, 400 mm 1,3 km/h and 2,2 km/h
Engine unit(s) 1500/1800 RPM		
Control		55 kW/55kW, 64 kW/73 kW, 66 kW/78 kW PLC – IP 67 LCD screen 4,3" & remote control
Smart sequential auto start/stop from remote control		•
Available drive systems		
	Diesel/hydraulic drive	•
	e-drive Diesel/hybrid, electric plug-in & plug-out	•
	ZERO drive (no combustion engine, plug-in electric)	•

OPTIONS

Feeding & screening	
Wear lining in hopper HB 450: 8 mm	•
Several hopper & corner extensions	•
XXL Hopper	/
Apron feeder (XXL)	/
Feed hopper with belt feeder	•
Inline belt feeder without hopper	/
Overband magnet for Inline belt feeder without hopper	/
Screen flow break	•
Anti clogging system	•
Fast tensioning system for upper deck screens	•
Canvas cover for screen box	•
Walkway beside screenbox	•
Wide range op screen media	•
Bivitex flip flow screen box	•
Volumetric belt scale on apron feeder	•
Conveyors	
Dust suppression system at conveyors	•
Picking station at oversize belt conveyor	Left & right side
Extra long oversize belt conveyor (discharge heigth)	1800mm longer (4000mm)
Over belt magnet on overbelt	•
Over belt magnet on side conveyors	/
Drum magnet and chute on side conveyors	•
Tungsten scrapers	Fines conveyor (left) Under Screen Conveyor
Other options	
Radio remote	•
Working lights	•
Fuel filling pump	•
Heating system for engine unit: diesel and hydraulic tank	•
Keestrack-er Telematics system UMTS/GPS	•
Lifting eyes	•

TRANSPORT	
Transport l x w x h (mm)	11296 x 2550 x 3330

LEGENDA	
•	applicable - available
/	not applicable- not available



METRIC



K5

FLIP FLOW

optional

IMPERIAL



The contractors choice due to heavy duty performance, compact transport and high productivity.

Its long screen deck is perfect for precision screening from scalping to fine screening.

The K5 has a large range of screening media available incl. the Bivitec flip flow screen box for very difficult to process materials. Perfect service access and a walkway on the left side of the screen box, which is liftable and can be set in several inclinations.

2 or 3-way split position possible

Extra long screenbox

3,43	2,37	1,05	36
US Gal/h	US Gal/h	US Gal/h	kWh

Applications

Pre-screening/scalping
 Screening behind or before a crusher
 Top soil
 Separation of "sticky" aggregate
 Construction and demolition waste
 Sand and gravel
 Quarrying and mining
 Coal
 Wood
 Recycling landfill
 And others

Increased uptime and longer service intervals due to Long Life Grease

Maintenance free Return drum bearings (greased for life)

Automatic transport locking system on side conveyors

- Hydraulic folding hopper of HB 450 steel
- Superiour level of surface treatment
- Accessable doors and panels on all sides of the machines for easy maintenance and repair
- Standard equipped with heavy duty apron feeder

Technical specifications	
Capacity up to	500 sT
Weight	31 sT
Screen box (l x w)	17' x 5' & 17' x 4,5'
Feed hopper in HB450	9,1 yard ³
Hydraulic folding hopper for transport	•
Heavy Duty Plate Apron Feeder	10'4" x 3'8"
Loading height	
open back wall	8'8"
half open back wall	9'11"
closed back wall	11'2"
Side loading length	13'9"
Screen box (l x w) standard & bivitec flip flow	17' x 5' & 17' x 4,5'
Upper deck m ²	80,7 ft ² & 72,7 ft ²
Middle deck m ²	/
Lower deck m ²	80,7 ft ² & 72,7 ft ²
Hydraulic liftable screenbox	•
Screen box can be set in several inclinations	6
Standard walkway beside screenbox	Left side
Standard Long Life Grease: grease interval every 250 h	•
Conveyor belts (l x w) & discharge height	
Oversize belt conveyor (discharge height)	16'5" x 3'11" (10'2")
Fine fraction belt conveyor (left) (discharge height)	27'5" x 2'11" (14'4")
Middle fraction belt conveyor (right) (discharge height)	27'2" x 2'8" (12'5")
Track-unit: Length, total width, track shoe width	10'10", 8'2", 1'2"
2-speed track drive	0,8/1,4 mph
Engine unit(s) 1500/1800 RPM	55 kW/55kW, 64 kW/73 kW, 66 kW/78 kW
Control	PLC – IP 67 LCD screen 4,3" & remote control
Smart sequential auto start/stop from remote control	•
Available drive systems	
Diesel/hydraulic drive	•
e-drive Diesel/hybrid, electric plug-in & plug-out	•
ZERO drive (no combustion engine, plug-in electric)	•

OPTIONS

Feeding & screening	
Wear lining in hopper HB 450: 8 mm	•
Several hopper & corner extensions	•
XXL Hopper	/
Apron feeder (XXL)	/
Feed hopper with belt feeder	•
Inline belt feeder without hopper	/
Overband magnet for Inline belt feeder without hopper	/
Screen flow break	•
Anti clogging system	•
Fast tensioning system for upper deck screens	•
Canvas cover for screen box	•
Walkway beside screenbox	•
Wide range op screen media	•
Bivitex flip flow screen box	•
Volumetric belt scale on apron feeder	•
Conveyors	
Dust suppression system at conveyors	•
Picking station at oversize belt conveyor	Left & right side
Extra long oversize belt conveyor (discharge heigth)	5'10" longer
Over belt magnet on overbelt	•
Over belt magnet on side conveyors	/
Drum magnet and chute on side conveyors	•
Tungsten scrapers	Fines conveyor (left) Under Screen Conveyor
Other options	
Radio remote	•
Working lights	•
Fuel filling pump	•
Heating system for engine unit: diesel and hydraulic tank	•
Keestrack-er Telematics system UMTS/GPS	•
Lifting eyes	•

TRANSPORT	
Transport l x w x h	37'1" x 8'4" x 10'11"

LEGENDA	
•	applicable - available
/	not applicable- not available



IMPERIAL